

Smith & Wesson[®] Handcuffs







HANDCUFFS

Model 100 - M&P Lever Lock

New Locking System!



MODEL 100 - M&P LEVER LOCK					
Wrist Opening:	2.04"	Weight:	10.0 oz		
First Notch Inside Perimeter:	8.40"	Locking Positions:	23		
Last Notch Inside Perimeter:	5.80"	Distance Between Cuffs:	2.00"		
Tightest Inside Width:	1.80"	Maximum Overall Length:	8.98"		
SKU: 350122 - Lever Lock,	Nickel*	SKU: 350150 - Lever Lock,	Melonite®		
* MEETS NIJ STANDARD 0307.01					

MODEL 1 - UNIVERSAL



MODEL 1 UNIVERSAL - CHAIN & HINGE						
Wrist Opening:	2.40"	Weight:	12.0 oz			
First Notch Inside Perimeter:	9.40"	Locking Positions:	31			
Last Notch Inside Perimeter:	5.80"	Distance Between Cuffs:	2.00"			
Tightest Inside Width:	1.60"	Maximum Overall Length:	9.85"			
SKU: 350132 - Chain, Pin Loc	k, Nickel	SKU: 350133 - Hinge, Pin Loc	k, Nickel			

Smith & Wesson Handcuffs are fabricated from the finest quality carbon or stainless steel. They are made with heat treated internal lockworks, featuring smooth ratchets for swift cuffing and double locks to prevent tampering. From the original Model 100 series handcuffs to the unmatched durability of our restraint chains and leg irons - Smith & Wesson is a proven worldwide leader in handcuff and restraint production.

Along with the key actuated lock, all of our handcuffs come with a double locking system. The double locking system is actuated by means of a slot lock, push pin lock or the new, patented M&P lever lock - depending on the model.

PATENTED M&P LEVER LOCK



With the tip of your finger, fully lift the lever and then allow it to return. Once this has been done, the double lock will be set. This causes the lock spring to move into a position that locks the bolt thus preventing the cuff from being further tightened. NO TOOL **REQUIRED TO DOUBLE LOCK!**

PUSH PIN LOCK



Using the small peg on the top of the key, fully depress the push pin. This will lock the bolt as described with the double slot lock. This causes the lock spring to move into a position that locks the bolt thus preventing the cuff from being further tightened.

SLOT LOCK



Insert the small peg on the top of the key into the double lock slot. In this position, the small peg can contact the end of the lock spring. Slide the key toward the key hole. This causes the lock spring to move into a position that locks the bolt thus preventing the cuff from being further tightened.

All Smith & Wesson Handcuffs meet the NIJ requirement pertaining to strength.



All Smith & Wesson Handcuffs are proudly made in U.S.A.

WHAT IS MELONITE[™]?

Melonite[™] is a treatment for improving the surface properties of metal parts. The result is an ultradurable, matte-black, scratch-resistant finish.



Smith & Wesson now offers a Model 100 handcuff with a Melonite[™] finish. Please visit smith-wesson.com to see other Melonite[™] products available.

MODEL 103 - STAINLESS STEEL



MODEL 103 & 103 P					
Wrist Opening:	2.04"	Weight:	10.0 oz		
First Notch Inside Perimeter:	8.40"	Locking Positions:	23		
Last Notch Inside Perimeter:	5.80"	Distance Between Cuffs:	2.00"		
Tightest Inside Width:	1.80"	Maximum Overall Length:	8.98"		
SKU: 350105 - Slot Lock, Stainless* SKU: 350136 - Pin Lock, Stainless*					
* MEETS NULSTANDARD 0307 01					

MEETS NIJ STANDARD 0307.01

MODEL 100



MODEL 100 & 100 P				
Wrist Opening:	2.04"	Weight:	10.0 oz	
First Notch Inside Perimeter:	8.40"	Locking Positions:	23	
Last Notch Inside Perimeter:	5.80"	Distance Between Cuffs:	2.00"	
Tightest Inside Width:	1.80"	Maximum Overall Length:	8.98"	
SKU: 350103 - Slot Lock, Nickel* SKU: 350101 - Slot Lock, Blue				
SKU: 350135 - Pin Lock, Nickel* SKU: 350155 - Slot Lock, Melonite®			lelonite®	

* MEETS NIJ STANDARD 0307.01

MODEL 104 - MAXIMUM SECURITY



MODEL 104 - MAXIMUM SECURITY CUFFS					
Wrist Opening:	2.04"	Weight:	10.0 oz		
First Notch Inside Perimeter:	8.40"	Locking Positions:	23		
Last Notch Inside Perimeter:	5.80"	Distance Between Cuffs:	2.00"		
Tightest Inside Width:	1.80"	Maximum Overall Length:	8.98"		
SKU: 350107 - Slot Lock, Nickel* SKU: 350137 - Pin Lock, Nickel*					

MEETS NIJ STANDARD 0307.01

MODEL 300



MODEL 300 & 300 P			
Wrist Opening:	2.04"	Weight:	10.0 oz
First Notch Inside Perimeter:	8.40"	Locking Positions:	23
Last Notch Inside Perimeter:	5.80"	Distance Between Cuffs:	2.00"
Tightest Inside Width:	1.80"	Maximum Overall Length:	8.13"
SKU: 350095 - Slot Lock, Bl	ue	SKU: 350096 - Slot Lock, N	lickel*
SKU: 350138 - Pin Lock, Nic	kel*	-	
* MEETS NIJ STANDARD 0307.01			

MODEL 110 - SPECIAL SECURITY



MODEL 110 - SPECIAL SECURITY					
Wrist Opening:	2.80"	Weight:	18.0 oz		
First Notch Inside Perimeter:	10.90"	Locking Positions:	24		
Last Notch Inside Perimeter:	8.10"	Distance Between Cuffs:	2.00"		
Tightest Inside Width:	2.50"	Maximum Overall Length:	11.24"		
SKU: 350118 - Slot Lock, Nickel		SKU: 350119 - Slot Lock, B	lue		

MODEL 100L - 4 LINK CHAIN



SKU: 350140 - Slot Lock, Nickel		SKU: 350141 - Slot Lock, B	lue
Tightest Inside Width:	1.80"	Maximum Overall Length:	10.23"
Last Notch Inside Perimeter:	5.80"	Distance Between Cuffs:	3.25"
First Notch Inside Perimeter:	8.40"	Locking Positions:	23
Wrist Opening:	2.04"	Weight:	10.0 oz
MODEL 100L - 4 LINK CHAIN			10.0

MODEL 1900 - Leg Irons



USES MODEL 110 HANDCUFFS

MODEL 1900 - LEG IRONS					
Ankle Opening:	2.80"	Weight:	22.0 oz		
First Notch Inside Perimeter:	10.90"	Locking Positions:	24		
Last Notch Inside Perimeter:	8.10"	Distance Between Cuffs:	17.30"		
Tightest Inside Width:	2.50"	Maximum Overall Length:	25.63"		
SKU: 350121 - Slot Lock, Stainless					

MODEL 1840 - RESTRAINT CHAIN



MODEL 1840 - RESTRAINT CHAIN

Chain Length: 60.0" - Accommodates Any

Standard Handcuff

- Adjustable to Fit

· **,** · · · · · ·

SKU: 350100 - Stainless Steel Restraint Chain

MODEL 1800 - RESTRAINT CHAIN



MODEL 1800 - RESTR	AINT CHAIN		
Handcuff: Mod	el 100 Slot Lock	Overall Chain Length:	54.0"
Distance Between Cuf	fs: 15.25"	Weight:	27.0 oz.
Cuff Distance From C	hain: 3.5"	-	
SKU: 350109 - Stain	less Steel Restrai	int Chain	

MODEL 1850 - RESTRAINT CHAIN



MODEL 1850 -	RESTRAINT CHAIN		
Handcuff:	Model 1 Pin Lock	Leg Iron:	Model 1900
Chain Length B	etween Handcuffs & Leg	Irons:	32.0"
SKU: 350139	- Stainless Steel Restrai	nt Chain	

COLOR HANDCUFFS

- PRISONER CATEGORIZATION
- DEPARTMENT OWNERSHIP
- OFFICER OWNERSHIP



An advanced, tough as nails, corrosion protection system. This system, when applied to the critical metal parts, makes the restraint nearly impervious to rust.

MODEL 100 - WEATHER SHIELD® COLOR CUFFS



MODEL 100 - RED WEATHER SHIELD® FINISH					
Wrist Opening:	2.04"	Weight:	10.0 oz		
First Notch Inside Perimeter:	8.40"	Locking Positions:	23		
Last Notch Inside Perimeter:	5.80"	Distance Between Cuffs:	2.00"		
Tightest Inside Width:	1.80"	Maximum Overall Length:	8.98"		
SKU: 350149 - Slot Lock, Red & Nickel					



MODEL 100 - PINK WEATHER SHIELD® FINISH				
Wrist Opening:	2.04"	Weight:	10.0 oz	
First Notch Inside Perimeter:	8.40"	Locking Positions:	23	
Last Notch Inside Perimeter:	5.80"	Distance Between Cuffs:	2.00"	
Tightest Inside Width:	1.80"	Maximum Overall Length:	8.98"	
SKU: 350144 - Slot Lock, Pink & Nickel				



MODEL 100 - YELLOW WEATHER SHIELD® FINISH				
Wrist Opening:	2.04"	Weight:	10.0 oz	
First Notch Inside Perimeter:	8.40"	Locking Positions:	23	
Last Notch Inside Perimeter:	5.80"	Distance Between Cuffs:	2.00"	
Tightest Inside Width:	1.80"	Maximum Overall Length:	8.98"	
SKU: 350145 - Slot Lock, Yellow & Nickel				



MODEL 100 - BLUE WEATHER SHIELD® FINISH				
Wrist Opening:	2.04"	Weight:	10.0 oz	
First Notch Inside Perimeter:	8.40"	Locking Positions:	23	
Last Notch Inside Perimeter:	5.80"	Distance Between Cuffs:	2.00"	
Tightest Inside Width:	1.80"	Maximum Overall Length:	8.98"	
SKU: 350146 - Slot Lock, Blue & Nickel				



MODEL 100 - GREEN WEATHER SHIELD® FINISH				
Wrist Opening:	2.04"	Weight:	10.0 oz	
First Notch Inside Perimeter:	8.40"	Locking Positions:	23	
Last Notch Inside Perimeter:	5.80"	Distance Between Cuffs:	2.00"	
Tightest Inside Width:	1.80"	Maximum Overall Length:	8.98"	
SKU: 350147 - Slot Lock, Green & Nickel				



MODEL 100 - DESERT WEATHER SHIELD® FINISH				
Wrist Opening:	2.04"	Weight:	10.0 oz	
First Notch Inside Perimeter:	8.40"	Locking Positions:	23	
Last Notch Inside Perimeter:	5.80"	Distance Between Cuffs:	2.00"	
Tightest Inside Width:	1.80"	Maximum Overall Length:	8.98"	
SKU: 350148 - Slot Lock, Desert & Nickel				



Handcuffs

HANDCUFFING INSTRUCTOR COURSE

The Smith & Wesson Academy[®] offers a Handcuffing Instructor Course. This course is designed to give the instructor the necessary background to conduct a comprehensive handcuffing program for his or her agency.

Handcuffing techniques are the centerpoint for many assaults on officers and there is much litigation concerning the use of force.

Please call 1-413-846-6461 for information on this course and the many others offered at the Smith & Wesson Academy[®]. Courses are offered in Springfield, MA and at many field schools around the world.

Visit smith-wesson.com for more details.



